



STOP READ THIS WARNING!

Make sure you test fit these exhaust components BEFORE any cutting, welding or unnecessary bending is done. Once modified, the components of the system are NOT RETURNABLE.

If you are unsure of the proper installation procedures or fitment, please contact a qualified exhaust shop or call our tech lines toll free at 800-421-3890 or visit our installation gallery at: www.pypesexhaust.com/install

One of our experienced exhaust techs will be glad to assist you in any way. Thanks and enjoy you new...

Pypes Performance Exhaust!

SCROLL DOWN FOR INSTRUCTIONS



Thanks for purchasing Pypes Performance Exhaust 409 Stainless Steel down-pipes.



*Pypes Performance Exhaust
2705 Clemens Rd B103 Hatfield, PA 19440
www.pypesexhaust.com 800-421-3890*

- These down-pipes are designed to connect to your factory manifolds and end at the transmission cross-member.
- On many applications, the down-pipe will need to be trimmed in length to end in the cross-member humps.
- Your new down-pipe is ball flared to connect to the ball on the manifold outlet. Sometimes, the outlet diameter on the manifold deteriorated from rust or wear, simply grind the ball flare on the down-pipe slightly to allow for correct sealing.
- On many applications, metal to metal contact is how the pipe seals, donut gaskets are not necessary.
- Pontiac Ram-Air manifold owners will be required to purchase the mounting flanges, part numbers:
PPF10 (Two 3 bolt flanges) or PPF12 (a 2 bolt and a 3 bolt flange).